

The Knox Standpipe Lock[®] protects standpipes, fire and wall hydrants from accidental damage, vandalism, and physical attack. Since the Knox Standpipe Lock holds water pressure, it can be installed on hydrants. The Knox Standpipe Lock is available for 2.5" connections with varying thread options and is operated with a Knox FDC Wrench controlled by the Fire Department.

FEATURES

- ✓ Standard threads are NH (3.068 X 7.5TPI) but can be customized to fit any 2.5" thread pattern
- ✓ Water-tight
- ✓ Heavy-duty stainless steel construction to resist against physical attack
- ✓ Stainless steel locking mechanism
- ✓ Brass threads to assist in ease of installation
- ✓ Authorized by 2018 IFC and IBC (Chapter 905.11)

BENEFITS

- ✓ Protects dry and wet standpipe outlets in stairwells from vandalism
- ✓ Reduces unauthorized cap removal and cap theft
- ✓ Assures uncompromised threads
- ✓ Discourages water theft
- ✓ Can be mounted onto fire hydrants

APPLICATIONS

- ✓ Wet and dry standpipes
- ✓ Fire hydrants
- ✓ Wall hydrants

ORDERING SPECIFICATIONS

To insure procurement and delivery of the Knox Standpipe Lock, it is suggested that the following specification paragraph be used:

Knox Standpipe Lock made of stainless steel.

Size: 2.5-inch

Construction: Stainless steel

Lock: Locks with a proprietary Knox FDC Wrench

P/N: 4043 (mfr's cat. ID)

Mfr's Name: KNOX COMPANY



2.5" Diameter, Female
Locking Cap

WEIGHT: 6.95 lb

WARNING:

This product must be installed by Authorized Fire Department representative or Fire Department-Authorized Contractor only. This is a security product that requires a special fire department keywrench to lock the cap in place. Unauthorized installation may result in improper locking of the cap. An improperly locked cap may be subject to removal by unauthorized personnel.